



4051 Rope-operated extension ladder, two-section

- › Inner width of the ladder 300 mm (upper section).
- › Rolled profile rungs.
- › Ladder feet pressed into the stile.
- › Maximum grip rope (Ø 10 mm), for safe height adjustment.
- › With high-quality plastic wall rollers.
- › Guide fittings made of solid steel.



Number of rungs		2×14	2×16	2×18	2×20
Stile	approx. mm	83	89	89	89
Number of rungs	at max. extension	25	29	32	36
Length	retracted approx. m	4.11	4.67	5.23	5.79
Length	extended approx. m	7.18	8.30	9.14	10.26
Standing height	approx. m	5.97	7.05	7.86	8.95
Working height	approx. m	7.47	8.55	9.36	10.45
Reach height	approx. m	7.97	9.05	9.86	10.95
Width	extended top/bottom approx. mm	355/425	355/425	355/425	355/425
Weight	approx. kg	17.8	22.5	25.5	29.4
EAN-Code		4019502339248	4019502339255	4019502339262	4019502339279
Order no.		405128	405132	405136	405140

For an explanation of working/standing/reach height see on page 5.

Recommended accessories:



Cross-beam for ladder section



Set of foot pikes for stiles



Telescopic wall spacer for rung ladders



Ladder holder set for gutters



Ladder bracket set for roof racks