



## 6011 Rung leaning ladder

- › Inner width of the ladder 370 mm.
- › Stiles of seamless extruded profiles with ergonomic shape.
- › Rungs made of extruded profiles with deep ribbing, and therefore increased slip resistance.
- › Ladder feet screwed to the stile (easily replaceable).
- › Stable stiffening braces on first step.



| Number of rungs |            | 6             | 7             | 8             | 9             | 10            | 12            | 14            | 16            | 18            | 20            | 22            |
|-----------------|------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|
| Stile           | approx. mm | 60            | 60            | 60            | 60            | 60            | 60            | 60            | 66            | 71            | 71            | 71            |
| Length          | approx. m  | 1.88          | 2.16          | 2.44          | 2.72          | 3.00          | 3.56          | 4.12          | 4.68          | 5.24          | 5.80          | 6.36          |
| Standing height | approx. m  | 0.82          | 1.09          | 1.36          | 1.63          | 1.90          | 2.44          | 2.98          | 3.52          | 4.06          | 4.60          | 5.14          |
| Working height  | approx. m  | 2.32          | 2.59          | 2.86          | 3.13          | 3.40          | 3.94          | 4.48          | 5.02          | 5.56          | 6.10          | 6.64          |
| Reach height    | approx. m  | 2.82          | 3.09          | 3.36          | 3.63          | 3.90          | 4.44          | 4.98          | 5.52          | 6.06          | 6.60          | 7.14          |
| Width           | approx. mm | 425           | 425           | 425           | 425           | 425           | 425           | 425           | 425           | 425           | 425           | 425           |
| Weight          | approx. kg | 3.3           | 3.8           | 4.2           | 4.6           | 5.2           | 6.3           | 7.3           | 8.0           | 10.0          | 11.2          | 12.5          |
| EAN-Code        |            | 4019502338234 | 4019502338241 | 4019502338258 | 4019502338265 | 4019502338272 | 4019502338296 | 4019502338302 | 4019502338319 | 4019502338326 | 4019502338333 | 4019502338340 |
| Order no.       |            | 601106        | 601107        | 601108        | 601109        | 601110        | 601112        | 601114        | 601116        | 601118        | 601120        | 601122        |

For an explanation of working/standing/reach height see on page 5.

### Recommended accessories:



P. 176

Cross-beam for ladder section



P. 177

Suspension hook set



P. 177

Suspension set