



## 4026 Step ladder with platform, single-sided accessible

- › Anodised stiles.
- › With spacious, practical tool tray made of high-strength plastic.
- › Bucket hook with 25 kg load-bearing capacity.
- › Steps flush with stile.
- › 80 mm step depth.
- › Anti-slip ladder feet.
- › Dimensions of platform 250×250 mm.
- › Stable stiffening braces on first step.



Number of steps incl. platform		3	4	5	6	7	8
Stile	approx. mm	55	55	55	55	55	55
Length	approx. m	1.37	1.62	1.87	2.12	2.36	2.61
Standing height (height to platform)	approx. m	0.65	0.88	1.11	1.35	1.58	1.80
Working height	approx. m	2.15	2.38	2.61	2.85	3.08	3.30
Reach height	approx. m	2.65	2.88	3.11	3.35	3.58	3.80
Total vertical height	approx. m	1.25	1.48	1.71	1.95	2.18	2.40
Width top/bottom	approx. mm	280/415	280/440	280/465	280/495	280/520	280/545
Base width	approx. m	0.70	0.85	1.00	1.15	1.30	1.50
Weight	approx. kg	4.0	4.9	5.6	6.4	7.4	7.9
EAN-Code		4019502339477	4019502339484	4019502339491	4019502339507	4019502339514	4019502339521
Order no.		402603	402604	402605	402606	402607	402608

### Spare parts:

- › Spare parts set tool tray, order no. 0054834, see on page 192.
- › Platform support repair set, order no. 0053991, see on page 189.

For an explanation of working/standing/reach height see on page 5.



## 6026 Step ladder with platform, single-sided accessible

- › Stable concept of D-shaped stiles for considerably higher feeling of safety when working on the step ladder and 4-times higher torsional stability of the stiles.
- › Deep aluminium tray with suspension possibility for bucket or small appliances.
- › The plastic cover of the support bracket prevents danger of pinching and protects against dirt in the hinge area.
- › Step depth 80 mm.
- › Two high-strength restraining straps as safety strut from size 6 upwards.
- › Dimensions of platform 250×250 mm.



Number of steps incl. platform		3	4	5	6	7	8	10
Stile	approx. mm	81	81	81	81	81	81	81
Length	approx. m	1.45	1.70	1.95	2.22	2.45	2.70	3.20
Standing height (height to platform)	approx. m	0.68	0.91	1.14	1.37	1.60	1.84	2.30
Working height	approx. m	2.18	2.41	2.64	2.87	3.10	3.34	3.80
Reach height	approx. m	2.68	2.91	3.14	3.37	3.60	3.84	4.30
Total vertical height	approx. m	1.33	1.56	1.79	2.02	2.25	2.49	2.95
Width top/bottom	approx. mm	305/450	305/475	305/500	305/525	305/550	305/575	305/625
Base width	approx. m	0.70	0.85	1.00	1.15	1.30	1.50	1.80
Weight	approx. kg	5.6	5.8	6.6	8.2	9.4	10.5	12.2
EAN-Code		4019502339743	4019502339750	4019502339767	4019502339774	4019502339781	4019502339798	4019502339804
Order no.		602603	602604	602605	602606	602607	602608	602610

### Spare parts:

- › Spare parts set hinge covers, order no. 0054963, see on page 186.
- › Platform support repair set, order no. 0053991, see on page 189.

For an explanation of working/standing/reach height see on page 5.